



DISPLAY FREEZER

Product Name: Display Freezer (2 Door) 2D/DF-SM-EV

- **Triple layer heated glass, frost free**
- **All display freezer** are with expansion valve (TX valve)
- **Internally lighted promotes impulse sales.** Shielded LED fluorescent internal lighting assures safety.
- **High-density Cyclo-isopentane Polyurethane** insulated body saves energy.
- **Refrigeration system protected from corrosion** by urethane-treated evaporator coil.
- **Environmental friendly refrigerant** (CFC and HCFC Free) R404a

Description

Model	1 Door	2 Door	3 Door
Silver Aluminium Door Frame	1D/DF-SG-EV	2D/DF-SG-EV	3D/DF-SG-EV
Temperature°C (celsius)	-20 to -14	-20 to -14	-20 to -14
External Dimension (mm)	635 x (710+20) x 2060	1260 x (710+20) x 2060	1880 x (710+20) x 2060
Gross Volume (Litres)	400	876	1351
Voltage/ Frequency (V/ Hz)	230V/ 1 / 50Hz	230V/ 1 / 50Hz	230V/ 1 / 50Hz
	220V/ 1 / 60Hz	220V/ 1 / 60Hz	220V/ 1 / 60Hz
Weight (kg)	113	199	279
Cooling Capacity	772	1112	1526
Wattage(W)	844 - 932	1412 - 1560	1849 - 2043
Ampere (A)	3.8 - 4.2	6.2 - 6.8	8.7 - 9.6
Energy Consumption (kw/ 24h)	18.7 - 20.7	31.2 - 34.5	44.9 - 49.6
Refrigerant	R404a	R404a	R404a
Unit For 20ft Container	24	12	9
Unit For 40ft Container	51	27	18