



**PERFEKT
700 TN**

TECNODOM^{spa}



0°C / +10°C

TN: Temperatura normale
Normal temperature

**DOM
SYS
TEM**

DOM SYSTEM

dotazione /set-up

**CONSERVATORI VERTICALI
700 L**

_IT

CARATTERISTICHE:

- Interno ed esterno in acciaio inossidabile, ad eccezione del fondo esterno, del soffitto esterno e dello schienale in acciaio zincato.
- Angoli arrotondati interni.
- Poliuretano ad alta pressione iniettato senza gas pericolosi per l'ambiente.
- Spessore di isolamento: 60 mm.
- Porte a chiusura automatica con guarnizioni magnetiche.
- Microinterruttore porta.
- Pannello di controllo anteriore elettronico con 2 sonde NTC.
- Raffreddamento ventilato.
- Unità di condensazione "monoblocco" tropicalizzata ed estraibile (temperatura ambiente + 40 ° C e umidità relativa del 60%) con gas R452A.
- Armadi refrigerati **TN** (Temperatura normale) progettati anche per unità di condensazione remota.
- Sbrinamento completamente automatico e condensazione dell'evaporazione dell'acqua.
- Porta reversibile.
- Piedini regolabili in acciaio inossidabile(110/190 H mm).

DOTAZIONE PER ALLESTIMENTO INTERNO:

- 3 kit ganci (4 ganci: 2 normali, 2 antiribalta).
- 3 griglie Rilsan rivestite in plastica GN 2/1.
- Microinterruttore porta.

_EN

FEATURES:

- Inside and outside made of Stainless Steel, except for external ottom, external ceiling and back made of Galvanized Steel.
- Internal rounded corners.
- High Pressure Polyurethane injected without hazardous gases for the environment.
- Insulation thickness: 60 mm.
- Selfclosing doors with magnetic gaskets.
- Door micro switch.
- Electronic front control panel with 2 NTC probes.
- Ventilated cooling.
- Tropicalized and extractable "monoblock type" condensing unit (ambient temperature +40°C and relative humidity of 60%) with gas R452A.
- Refrigerated **TN** (Normal temperature) cabinets designed also for remote condensing unit.
- Completely automatic defrosting and condense water evaporation.
- Reversible door.
- Adjustable Stainless Steel feet (110/190 H mm).

EQUIPEMENT FOR INTERIOR CONSTRUCTION:

- 3 hooks kit (4 hooks: 2 normal, 2 anti-tipping).
- 3 plastic coated Rilsan grids GN 2/1.
- Door micro switch.

Cod. AF07PKMTN

Conservatori Verticali standard GN 2/1, monoblocco, in Acciaio Inox a temperatura normale.

Vertical conservatories standard GN 2/1, monobloc, in stainless steel at normal temperature.



GASTRONOMIA
GASTRONOMY



CARNE
MEAT



PASTICCERIA
BAKERY



SALUMI
COLD CUTS



FRUTTA E VERDURA
FRUITS VEGETABLES



PESCE
FISH



LATTICINI
DAIRY PRODUCT



CARNE
PRECONFEZIONATA
PREPACKED-MEAT



FARMACIA
PHARMACY



PESCE
PRECONFEZIONATO
PRE-PACKED FISH

CARATTERISTICHE TECNICHE / TECHNICAL FEATURES

DIMENSIONI - DIMENSIONS:	W 710 x D 800 x H 2030/2100 mm
DIMENSIONI IMBALLO - PACKAGING DIMENSIONS:	W 740 x D 850 x H 2200 mm
PESO NETTO - NET WEIGHT:	110 Kg
CAPACITA' NETTA - NET CAPACITY:	590 Lt
TEMPERATURA D'ESERCIZIO - WORKING TEMPERATURE:	0°C / +10°C
GAS REFRIGERANTE - GAS:	GAS R452A
COLLAUDO - TEST DETAILS:	+40°C / 60% RH
ASSORBIMENTO ELETTRICO - ABSORBED POWER:	385W
	963,12 kWh/year
ALIMENTAZIONE - POWER SUPPLY:	V-P-Hz 230-1-50

