

[Home](#) / [COMMERCIAL REFRIGERATION](#) / [COUNTER RANGE](#) / [DUAL COUNTER CHILLER & FREEZER](#)



DUAL COUNTER CHILLER & FREEZER

Product Name: Dual Counter Chiller & Freezer (2 Door)

- **High-density Cyclo-isopentane Polyurethane** insulated body saves energy.
- **Insulated partition between** left freezer and right chiller compartment ensures temperature integrity of each product zone.
- **Refrigeration system protected from corrosion** by urethane-treated evaporator coil.
- **Effective counter – balanced weight system** self-closing door provides smooth, even, positive closure.
- **Environmentally friendly refrigerant** (CFC and HCFC Free) R134a and R404a

MODEL	2 Door - 4' BS2DCF4/Z	2 Door - 5' BS2DCF5/Z	2 Door - 6' BS2DCF6/Z	3 Door - 7' BS3D2C1F7/Z	3 Door - 8' BS3D2C1F8/Z
Temperature°C (celsius) - Chiller - Freezer	+1 to +6 -20 to -14	+1 to +6 -20 to -14	+1 to +6 -20 to -14	+1 to +6 -20 to -14	+1 to +6 -20 to -14
External Dimension (mm)	1200 x 760 x 840	1500 x 760 x 840	1800 x 760 x 840	2100 x 760 x 840	2400 x 760 x 840
Gross Volume (Litres) - (Left) Freezer - (Right) Chiller	127 127	178 178	230 230	183 375	224 445
Voltage/Frequency (V/ Hz)	230v / 1 / 50Hz	230v / 1 / 50Hz	230v / 1 / 50Hz	230v / 1 / 50Hz	230v / 1 / 50Hz
	220v / 1 / 60Hz	220v / 1 / 60Hz	220v / 1 / 60Hz	220v / 1 / 60Hz	220v / 1 / 60Hz
Cooling Capacity (W)	382	415	415	680	680
Wattage (W)	371 - 409	418 - 462	456 - 504	462 - 510	474 - 522
Ampere(A)	2.5 - 2.7	2.8 - 3.2	3.0 - 3.4	3.1 - 3.5	3.3 - 3.7
Refrigerant	R404a	R404a	R404a	R404a	R404a
Defrost System	Electric Heater	Electric Heater	Electric Heater	Electric Heater	Electric Heater
Weight (kg)	88	107	119	141	151
Unit For 20ft Container	22	20	14	14	8
Unit For 40ft Container	46	42	28	28	16