



HIGH-EFFICIENT SOFTMOUNT WASHER-EXTRACTORS

IY350
35KG

IY450
45KG

IY600
60KG

FEATURES

- Freestanding, high spin
- Stainless steel cabinet (except top front panel)
- Stainless steel drum and tub
- Aries Elite- Fully programmable microprocessor
- Large door opening (Ø54 cm) for easy loading and unloading
- Large drain valves (2 x Ø 76 mm)
- Frequency controlled motor
- Perforated lifting ribs: more mechanical action, lower water consumption
- Eco washing programs - significantly reduces water and electricity consumption
- Liquid soap print
- Soap hopper with 5 removable compartments
- Economic height of door enables easy access with trolleys
- User friendly control position regardless user's height
- Bumper (front side protection)

OPTIONS

- Stainless steel top front panel
- Liquid soap pumps
- Aries Assist
- Weighing system by cells
- Recycle drain valve
- Isolation for energy and noise reduction
- Extra signalization (orange light + sound)
- Steam heating version
- Air operated water inlets
- Water sample
- 3rd water inlet, high inlets capacity
- USB & RS485 plug (combined on the back panel)



ROBUST DESIGN



LARGE DOOR
OPENING



LARGE DRAIN
VALVE

THE SMART LAUNDRY PARTNER

	IY350	IY450	IY600
INNERDRUM			
CAPACITY 10:1 (KG)	35	45	60
CAPACITY 9:1 (KG)	39	50	67
VOLUME (L)	350	450	600
DIAMETER (MM)	914	914	1035
DRUM SPEED			
WASH (RPM)	45	45	42
EXTRACTION (RPM)	839	839	788
G-FACTOR	360	360	360
MOTOR			
POWER (KW)	4	7,5	7,5
PROGRAMMER			
ARIES ELITE	standard	standard	standard
TILTING			
FORWARD TILTING	N/A	option	option
HEATING			
100% HOT WATER (°C)	90	90	90
100% ELECTRICAL (KW)	24	36	54
STEAM HIGH PRESSURE (BAR)	3-8	3-8	3-8
CONNECTIONS			
ELECTRICAL	3 x 200-240/50-60Hz 3 x 380-415/50-60Hz 3 x 440-480/50-60Hz	3 x 200-240/50-60Hz 3 x 380-415/50-60Hz 3 x 440-480/50-60Hz	3 x 200-240/50-60Hz 3 x 380-415/50-60Hz 3 x 440-480/50-60Hz
WATER INLET (MM)	3 x 25 (1")	3 x 25 (1")	3 x 25 (1")
STEAM INLET (MM)	19 (3/4")	19 (3/4")	19 (3/4")
DRAIN DIAMETER (MM)	2 x 76 (3")	2 x 76 (3")	2 x 76 (3")
TRANSPORT DATA			
GROSS WEIGHT (KG)	1170	1490	1640
GROSS WEIGHT WITH TILTING (KG)	N/A	1530	1680
NET WEIGHT (KG)	1010	1350	1500
NET WEIGHT WITH TILTING (KG)	N/A	1390	1540
DIMENSIONS H x W x D (MM)	1925 x 1315 x 1270	1925 x 1315 x 1502	1925 x 1315 x 1502
PACKING DIMENSIONS H x W x D (MM)	2125 x 1425 x 1470	2125 x 1425 x 1700	2125 x 1425 x 1700

Standard = standard version. * Tested in accordance of EN604-56 norm.
The data concerning dimensions of machines include all extended parts.

