

US type table top GAS RANGE LASTEST SERIES

Counter Top Open Burner



HWS-2

2 head open burner

Model#	HWS-2
Product dimension	308x744x344mm
Burner	2
Power	30000BTUx2=60000BTU/17.58KW
Gas Consumption	NG: 1.578m ³ /hour LPG: 0.6798m ³ /hour
Burner type	American type
Burner material	Cast Iron
Net Weight	29.5kg



HWS-4

4 head open burner

Model#	HWS-4
Product dimension	613x744x344mm
Burner	4
Power	30000BTUx4=120000BTU/35.16KW
Gas Consumption	NG: 3.156m ³ /hour LPG: 1.3596m ³ /hour
Burner type	American type
Burner material	Cast Iron
Net Weight	51kg



Beautiful, Practical and Durable



HWS-6

6 head open burner

Model#	HWS-6
Product dimension	613x744x344mm
Burner	6
Power	30000BTUx6=180000BTU/52.75KW
Gas Consumption	NG: 4.735m ³ /hour LPG: 2.0393m ³ /hour
Burner type	American type
Burner material	Cast Iron
Net Weight	77kg

Counter Top Gas Griddle



HERG-24

24" Gas Griddle

Model#	HERG-24
Product dimension	610x789x405mm; 24"x31.05"x15.96"
Griddle dimension	606x564mm, thickness=1inch; 25mm
Power	30000BTUx2=60000BTU/17.58KW
Gas Consumption	NG: 1.578m ³ /hour LPG: 0.6798m ³ /hour
Burner type	American type; Cast Iron



HERG-36

36" Gas Griddle

Model#	HERG-36
Product dimension	910x789x405mm; 36"x31.05"x15.96"
Griddle dimension	906x564mm, thickness=1inch; 25mm
Power	30000BTUx3=90000BTU/26.37KW
Gas Consumption	NG: 2.367m ³ /hour LPG: 1.0197m ³ /hour
Burner type	American type; Cast Iron

Key Features

- New **Family-Style** countertop design
- U Shape Stainless steel Hi power burner
- Griddle plate thickness=1 inch, full edge with Robot Hand Laser welding
- Stainless steel panel for full cover
- Gas Valve with CSA certificate
- Heavy duty Knob and Height adjustable legs



HERG-48

48" Gas Griddle

Model#	HERG-48
Product dimension	1210x789x405mm; 48"x31.05"x15.96"
Griddle dimension	1206x564mm, thickness=1inch; 25mm
Power	30,000BTUx4=120,000BTU/35.17KW
Gas Consumption	NG: 3.156m ³ /hour LPG: 1.36m ³ /hour
Burner type	American type; Cast Iron



HERG-60

60" Gas Griddle

Model#	HERG-60
Product dimension	1510x789x405mm; 60"x31.05"x15.96"
Griddle dimension	1506x564mm, thickness=1inch; 25mm
Power	30,000BTUx5=150,000BTU/43.96KW
Gas Consumption	NG: 3.945m ³ /hour LPG: 1.699m ³ /hour
Burner type	American type; Cast Iron

THERMOSATICT Gas Griddle

- Control by ITALY SABAF Thermosatic Gas Valve
- Built-in Probe, more accurate temperature
- Temp. range: 200°F -450°F



HERG-24T

24" Gas Griddle

Model#	HERG-24T
Product dimension	610x789x405mm; 24"x31.05"x15.96"
Griddle dimension	606x564mm, thickness=1inch; 25mm
Power	30000BTUx2=60000BTU/17.58KW
Gas Consumption	NG: 1.578m ³ /hour LPG: 0.6798m ³ /hour
Burner type	American type; Cast Iron
Temp range	200°F -450°F



HERG-48T

48" Gas Griddle

Model#	HERG-48T
Product dimension	1210x789x405mm; 48"x31.05"x15.96"
Griddle dimension	1206x564mm, thickness=1inch; 25mm
Power	30,000BTUx4=120,000BTU/35.17KW
Gas Consumption	NG: 3.156m ³ /hour LPG: 1.36m ³ /hour
Burner type	American type; Cast Iron
Temp range	200°F -450°F



HERG-36T

36" Gas Griddle

Model#	HERG-36T
Product dimension	910x789x405mm; 36"x31.05"x15.96"
Griddle dimension	906x564mm, thickness=1inch; 25mm
Power	30000BTUx3=90000BTU/26.37KW
Gas Consumption	NG: 2.367m ³ /hour LPG: 1.0197m ³ /hour
Burner type	American type; Cast Iron
Temp range	200°F -450°F



HERG-60T

60" Gas Griddle

Model#	HERG-60T
Product dimension	1510x789x405mm; 60"x31.05"x15.96"
Griddle dimension	1506x564mm, thickness=1inch; 25mm
Power	30,000BTUx5=150,000BTU/43.96KW
Gas Consumption	NG: 3.945m ³ /hour LPG: 1.699m ³ /hour
Burner type	American type; Cast Iron
Temp range	200°F -450°F