

FABRICANTES DE MOLINOS DE CAFÉ

MANUFACTURERS
OF COFFEE GRINDERS

Molino de café profesional para todo tipo de cafés

Professional coffee grinder for all types of coffee.

MOVIE TRON"63dB"

ABS

COLLECTION SILENCER





CARACTERÍSTICAS TÉCNICAS 0-500gr/3' Max 4Kg

VOLTAGE: 230V / 220V / 110V
FREQUENCY: 50Hz / 60Hz
PHASES: 1 (monophasic)
RPM: 1:300 / 1.600
CURRENT: 2,1A / 4,7A
CAPACITOR: 14µf / 55µf
POWER: 0,37Hp / 497W
PROTECTION RATING: IP21
MOTOR SUPPLIED WITH THERMAL PROTECTOR

MAXIMUM OPERATING TIME: 30 min

TEMPERED STEEL GRINDING WHEELS (62HRc) \varnothing 65mm LIFESPAN OF GRINDING WHEELS: 500 Kg

HOPPER CAPACITY: 1,5 Kg

MULTI-LANGUAGE TOUCH SCREEN

SELECTION FOR 1 OR 2 FRESHLY GROUND COFFEES OR CONTINUOUS GRINDING

TOTAL OR PARTIAL COFFEE COUNTER
ASSISTANT TIMER GRINDING POINT

DIMENSIONS WIDTH X LENGTH X HEIGHT: 270X460X630mm

WEIGHT: 13 Kg





460mm







MAIN ATTRIBUTES

Hopper (1,5kg) made of unbreakable and non-deformable material (co.polyester), with fast lock system and self-levelling when off the coffee grinder, with the possibility of cleaning in a dishwasher at 90 °C. - Micrometric regulation of the coffee grind using a regulatory pawl. - New expulsion system for the ground coffee (always leaving the grinding cavity clean when the coffee grinder stops). - Touch screen for easy programming and use (Language selection – Setting the grinding program for each dose – Selection of 1 dose, 2 doses or continuous grinding – Coffee counter: total or partial consumption). –Universal coffee tamper (rotatable) - Bodywork manufactured in anti-scratch material, in a single piece (less vibrations, more robustness). With ventilation system (internal air inlet and outlet). Large tray integrated into the body, ready to take knocks (portalter). - Hardened steel grinding blades (62/65 HRc) of 65mm diameter. - Motor assembly with anti-vibration system. - Silencer motor with internal auto-ventilation, 63dB.

Optional: Optional personalisation system with chrome plates on the doser and on the rear of the bodywork.

