

TECHNICAL CARD		
power supply	Monofase	
Volts	V 230/1	
frequency (Hz)	50	
motor power capacity (Kw)	0,495	
net weight (Kg)	102	
breadth (mm)	1870	
depth (mm)	700	
height (mm)	850	

## PROFESSIONAL DESCRIPTION

## REFRIGERATED TABLE 3 DOORS, capacity 460 litres, operating temperature 0°/+10°C, TECNODOM brand :

- **internal and external structure in Stainless Steel** , with the exception of the external bottom in Galvanized Steel;
- rounded internal corners;
- compartments suitable for inserting Gastro-Norm 1/1 grills or trays (530x325 mm);
- o capacity liters 460;
- operating temperature 0°/+10°C;
- insulation in CFC-free polyurethane, injected at high pressure;
- insulation thickness : 40 mm ;
- doors with automatic closing and magnetic seal;
- front electronic control panel with NTC probe;
- ventilated refrigeration;
- $\circ \ \ removable \ and \ tropicalized \ monobloc \ refrigeration \ unit \ as \ standard \ (ambient \ temperature \ +43°C \ and \ relative \ humidity \ of \ 65\%);$
- o works with R404A/R507 gas;
- $\circ~$  fully automatic defrosting and evaporation of condensation water ;
- Stainless Steel feet adjustable in height (110/190 H mm);
- o dim.mm.1870x700x850/920h.

## Supplied:

- 1 Rilsan GN 1/1 grill
- o 2 L-shaped stainless steel guides per door.

## CE mark Made in Italy

CODE	DESCRIPTION	PRICE/DELIVERY
TD-TF03MIDGN	REFRIGERATED TABLE 3 doors, TECNODOM brand, capacity 460 litres, operating temperature 0°/+10°C, ventilated refrigeration, Gastro-Norm 1/1, V.230/1, Kw.0,495, Weight 102 Kg, dim .mm.1870x700x850h	