



OPTIMIZED FOR

Baking tray 40x60cm
Teglia del formato 40x60cm


H17,5

 H17,5									
 MECHANICAL MECCANICO		TRAYS 6L GLASS		TRAYS 66L GLASS		TRAYS 9 GLASS		TRAYS 99 GLASS	
 CHAMBERS CAMERE	n°	1	 Ø40	2		1	 Ø35	2	
 PIZZE PIZZE	n°		 + 				 + 		
 TRAYS 40X60 TEGLIE 40X60	n°		 + 				 + 		
 WORKING TEMPERATURE TEMPERATURA D'ESERCIZIO	°C	50 - 450	50 - 450	50 - 450	50 - 450	50 - 450	50 - 450	50 - 450	50 - 450
 POWER POTENZA	kW	10,2	20,4	15,3	30,6				
 TOP	W	1700x3	1700x6	2550x3	2550x6				
 BOTTOM	W	1700x3	1700x6	2550x3	2550x6				
 POWER SUPPLY ALIMENTAZIONE	volt	230 - 400	230 - 400	230 - 400	230 - 400				
 ELECTRICAL ABSORPTION SINGLE PHASE ASSORBIMENTO MONOFASE	Amp x phase	44,3	88,7	66,5	133,0				
 ELECTRICAL ABSORPTION THREE PHASE ASSORBIMENTO TRIFASE	Amp x phase	14,8	29,6	22,2	44,3				
 INTERNAL DIMENSIONS DIMENSIONI INTERNE	 W  D  H	cm 123,0 84,0 17,5	123,0 84,0 17,5	123,0 108,0 17,5	123,0 108,0 17,5				
 EXTERNAL DIMENSIONS DIMENSIONI ESTERNE	 W  D  H	cm 150,0 108,0 41,5	150,0 108,0 74,5	150,0 132,0 41,5	150,0 132,0 74,5				
 PACKING DIMENSIONS DIMENSIONI IMBALLO	 W  D  H	cm 154,0 114,0 57,0	154,0 114,0 90,0	158,0 142,0 57,0	158,0 142,0 90,0				
 NET WEIGHT PESO NETTO	kg	127,0	225,0	178,0	307,0				
GROSS WEIGHT PESO LORDO	kg	144,0	247,0	207,0	340,0				
 DIGITAL VERSION VERSIONE DIGITALE		o	o	o	o				
 12V TRANSFORMER AND LAMP HOLDER TRASFORMATORE 12V E PORTALAMPADA		o	o	o	o				
 INTERNAL LIGHT LUCE INTERNA		•	•	•	•				
 REFRACTORY STONE HOB PIANO DI COTTURA IN PIETRA REFRATTARIA		•	•	•	•				
 OPTIONAL REFRACTORY STONE PIETRA REFRATTARIA OPZIONALE		o	o	o	o				
 STEAM GENERATOR VAPORIERA		o	—	o	—				

• As standard | Di serie o Optional | Opzionale