



# INDUSTRIAL TUMBLE-DRYER

IDR250

11 KG

IDR285

13 KG

IDR345

16 KG

## FEATURES


- Standard stainless steel drum with large diameter
- Easy-to-use microprocessor (ECT)
- Combination of radial and axial airflow
  - maximal heat transfer
  - low energy consumption
  - short drying time
- Large door opening for easy loading and unloading
- Self cleaning lint screen

## OPTIONS

- Reverse drum
- Flex Control Programmer (FCT)
- Residual moisture control
  - safe drying of delicate linen
  - humidity detection in %
  - ideal in combination with Softwash®
  - Ideal for dry cleaners, fire departments
  - available on Easy and Flex Control
- Stainless steel front



LARGE DOOR  
OPENING



ENERGY  
EFFICIENT



STANDARD  
STAINLESS  
STEEL DRUM

YOUR SMART LAUNDRY PARTNER

|                                          | IDR250                                                                                                              | IDR285                                                                                         | IDR345                   |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|--------------------------|
| DRUM                                     |                                                                                                                     |                                                                                                |                          |
| CAPACITY (KG)                            | 11                                                                                                                  | 13                                                                                             | 16                       |
| VOLUME (L)                               | 250                                                                                                                 | 285                                                                                            | 345                      |
| DIAMETER (MM)                            | Ø760                                                                                                                |                                                                                                | Ø760                     |
| NUMBER OF DRUMS                          | 1                                                                                                                   |                                                                                                | 1                        |
| NUMBER OF LOADING DOORS                  | 1                                                                                                                   |                                                                                                | 1                        |
| DRYING PERFORMANCE                       |                                                                                                                     |                                                                                                |                          |
| AIRFLOW (M³/H)                           | 520                                                                                                                 | 550                                                                                            | 600                      |
| DRYING AVERAGE (L/MIN)                   | 0,166 (EL) / 0,187 (G)                                                                                              | 0,206 (EL) / 0,223 (G)                                                                         | 0,260 (EL) / 0,270 (G)   |
| GAS HEATING                              |                                                                                                                     |                                                                                                |                          |
| GAS CONNECTION (IN)                      | 3/4"                                                                                                                |                                                                                                | 3/4"                     |
| ELECTRICAL CONNECTION - gas heating      | 1x 208-240V 50Hz, 3x 208-240V 50Hz, 3x 380-415V +N 50Hz, 3x 380-415V 50Hz, 3x 440V 60Hz, 3x 480V 50Hz, 3x 480V 60Hz |                                                                                                |                          |
| GAS OUTPUT (KW)                          | 16,5                                                                                                                | 19,5                                                                                           | 25                       |
| ELECTRICAL HEATING                       |                                                                                                                     |                                                                                                |                          |
| ELECTRICAL CONNECTION - electric heating | 3x 208-240V 50Hz, 3x 380-415V 50Hz, 3x 440V 60Hz, 3x 480V 60Hz                                                      |                                                                                                |                          |
| ENERGY (kW)                              | 13,5                                                                                                                | <b>13,5</b> / 18,0                                                                             | <b>18,0</b> / 24,0       |
| STEAM HEATING                            |                                                                                                                     |                                                                                                |                          |
| STEAM CONNECTION (NPT)                   | 3/4"                                                                                                                | 3/4"                                                                                           | 3/4"                     |
| ELECTRICAL CONNECTION- steam heating     | 3x220-240V 50Hz, 1x220-240V 50Hz, 3x380-415V 50Hz                                                                   | 1x 208-240V 50Hz, 3x 208-240V 50Hz, 3x 380-415V 50Hz, 3x 440V 650Hz 3x 480V 50Hz, 3x 480V 60Hz |                          |
| STEAM OUTPUT * (kW)                      | 16,6 - 19,4 / 20,0 - 23,3                                                                                           | 25,5 - 29,9 / 21,5 - 24,0                                                                      | 25,5 - 35,6 / 24,8 -27,7 |
| STEAM PRESSURE (BAR)                     | 3-6/7-10                                                                                                            | 3-6/7-10                                                                                       | 3-6/7-10                 |
| MOTOR                                    |                                                                                                                     |                                                                                                |                          |
| FAN (KW)                                 | 0,55                                                                                                                | 0,55                                                                                           | 0,55                     |
| DRIVE (KW)                               | 0,25                                                                                                                | 0,25                                                                                           | 0,25                     |
| PROGRAMMER                               |                                                                                                                     |                                                                                                |                          |
| EASY CONTROL- antivandal (ECT)           | Standard                                                                                                            | Standard                                                                                       | Standard                 |
| FLEX CONTROL                             | Available                                                                                                           | Available                                                                                      | Available                |
| DIMENSIONS                               |                                                                                                                     |                                                                                                |                          |
| H X W X D (MM)                           | 1680 x 795 x 1070                                                                                                   | 1680 x 795 x 1160                                                                              | 1680 x 795 x 1280        |
| NET WEIGHT (KG)                          | 225                                                                                                                 | 225                                                                                            | 240                      |
| TRANSPORT DATA                           |                                                                                                                     |                                                                                                |                          |
| PACKED H X W X D (MM)                    | 1785 x 855 x 1100                                                                                                   | 1785 x 855 x 1190                                                                              | 1785 x 855 x 1310        |
| GROSS WEIGHT (KG)                        | 245                                                                                                                 | 250                                                                                            | 260                      |

\* Steam output is flexible depending on steam pressure, The data concerning dimensions of machines include all extended parts

